



DOORS • GATES • ACCESS CONTROL

 **INTESSA**  
Innovation through Technology



DOCK LEVELER WITH HINGED LIP

**Rubber bumpers** provide safe approach of trucks to the loading place and prevent damage to the building walls. They cushion a shock in case of incorrect parking. The bumpers are made of technical rubber, which increases their wear resistance and durability.

The following models of bumpers are available:

- large bumper (500 x 250 x 100 mm)



# TECHNICAL SPECIFICATIONS

## DOCK LEVELER WITH HINGED LIP OF DLHHI SERIES

TECHNICAL SPECIFICATIONS	
Length, mm	2 000/2 500/3 000/3 500/4 000/4 500
Width, mm	1 800/2 000/2 200
Lip length, mm	400 (500 — option)
Working range, mm	from -350 to +550
Quantity of lift cylinders	one as standard / two upon request
Load capacity, kg	6 000/10 000 (other upon request)
Operating temperature range, °C	-20...+50**
Power supply, kW	1.1
Power voltage, V	380 as standard / 220 upon request (only with control unit DCUH-1)
Current frequency, Hz	50 as standard / 60 upon request
Oil, L	4 (Mobil Nuto H46 or analog)
Colour*	black (RAL 9005) and blue (RAL 5005), other upon request

\* Powder painting of frame and framework with preliminary shot blasting.  
 \*\* It's necessary to use low temperature oil if temperature is below -20 °C.

## DOCK LEVELER WITH HINGED LIP CANTILEVERED TYPE OF DLHHI(C) SERIES

TECHNICAL SPECIFICATIONS	
Length, mm	2 000/2 500/3 000/3 500
Width, mm	1 800/2 000/2 200
Lip length, mm	400 (500 — option)
Quantity of lift cylinders	one as standard
Load capacity, kg	6 000/10 000 (other upon request)
Operating temperature range, °C	-20...+50**
Power supply, kW	1.1
Power voltage, V	380 as standard / 220 upon request (only with control unit DCUH-1)
Current frequency, Hz	50 as standard / 60 upon request
Oil, L	4 (Mobil Nuto H46 or analog)
Colour*	black (RAL 9005) and blue (RAL 5005), other upon request

\* Powder painting of frame and framework with preliminary shot blasting.  
 \*\* It's necessary to use low temperature oil if temperature is below -20 °C.

# WORKING RANGE OF DOCK LEVELLERS

## DOCK LEVELER WITH HINGED LIP

		L, mm					
DLHHI		2 000	2 500	3 000	3 500	4 000	4 500
7	A,mm	220	293	346	405	465	525
Above	B,mm	602	676	730	785	855	915
Below	C,mm	314	293	299	295	380	380

